

An Efficient Solution to 3-COL with Tissue P Systems

Daniel Díaz-Pernil, Miguel A. Gutiérrez-Naranjo
Mario J. Pérez-Jiménez, Agustín Riscos-Núñez

Dpto. de Ciencias de la Computación e Inteligencia Artificial
E.T.S. Ingeniería Informática. Universidad de Sevilla
Avda. Reina Mercedes s/n, 41012, Sevilla, España
{sbdani, magutier, marper, ariscosn}@us.es

Abstract

In the literature, several examples of the efficiency of cell-like P systems regarding the solution of NP-complete problems in polynomial time can be found (obviously, trading space for time). Recently, different new models of tissue-like P systems have received important attention from the scientific community. In this paper we present a linear-time solution to an NP-complete problem from graph theory, the 3-COL problem, and we discuss the suitability of tissue-like P systems as a framework to address the efficient solution to intractable problems.

1 Introduction

Membranes are involved in many reactions taking place inside various compartments of a cell, and they act as selective channels of communication between different compartments as well as between the cell and its environment [1].

This paper is enclosed in the Natural Computing framework. More precisely, in the study of the structure and functioning of cells as living organisms able to process and generate information. Assuming this starting point, two different disciplines within Natural Computing can be found in the literature: *Membrane Computing* and *Brane Calculi*.

Brane Calculi was recently introduced in [6], under the assumption that in living cells membranes are not merely containers, but they are actually highly dynamic and participate actively on the cell life. In this way, “computation” happens on the membranes, not inside them.

On the other hand, Membrane Computing starts from the assumption that the processes taking place within the compartmental structure of a living cell can be interpreted as computations [18].

This emergent cross-disciplinary branch of Natural Computing was introduced by Gh. Păun in [17]. It has received important attention from the

scientific community since then, with contributions by computer scientists, biologists, formal linguists and complexity theoreticians, enriching each others with results, open problems and promising new research lines. In fact, Membrane Computing has been selected by the Institute for Scientific Information, USA, as a fast *Emerging Research Front* in Computer Science, and [19] was mentioned in [29] as a highly cited paper in October 2003.

The devices of this model are called *P systems*. Roughly speaking, a P system consists of a membrane structure, in the compartments of which one places multisets of objects which evolve according to given rules in a synchronous non-deterministic maximally parallel manner¹.

In the last years, many different models of P systems have been proposed. The most studied variants are characterized by a *cell-like* membrane structure, where the communication happens from a membrane to the surrounding one. In this model we have a set of nested membranes, in such a way that the graph of neighborhood relation is a tree.

One of the topics in the field is the study of the computational power and efficiency of P systems. In particular, different models of these cell-like P systems have been successfully used in order to design solutions to **NP**-complete problems in polynomial time (see [10] and references therein). These solutions are obtained by generating an exponential amount on workspace in polynomial time and using parallelism to check simultaneously all the candidates to solution. Inspired in living cells, cell-like P systems abstract the way of obtaining new membranes, mainly from two biological processes: *mitosis* (membrane division) and *autopoiesis*, see [14] (membrane creation). Both ways of generating new membranes have given rise to the corresponding P systems model: *P systems with active membranes*, where the new workspace is generated by membrane division and *P systems with membrane creation*, where the new membranes are created from objects.

Both models are universal from a computational point of view, but technically, they are pretty different. In fact, nowadays there does not exist any theoretical result which proves that these models can simulate each other in polynomial time.

Under the hypothesis $\mathbf{P} \neq \mathbf{NP}$, Zandron et al. [28] established the limitations of P systems that do not use membrane division concerning the efficient solution of **NP**-complete problems. This result was generalized by Pérez Jiménez et al. [23] obtaining a characterization of the $\mathbf{P} \neq \mathbf{NP}$ conjecture by the polynomial time unsolvability of an **NP**-complete problem by language accepting P systems (without membrane division rules).

We shall focus here on another type of P systems, the so-called (because of their membrane structure) *Tissue P Systems*. Instead of considering that membranes are hierarchically arranged, the membranes are placed in the nodes of a graph. This variant has two biological inspirations (see [16]): intercellular communication and cooperation between neurons. The common mathematical model of these two mechanisms is a net of processors dealing with symbols

¹A layman-oriented introduction can be found in [20] and further bibliography at [30].

and communicating these symbols along channels specified in advance. The communication among cells is based on symport/antiport rules². Symport rules move objects across a membrane together in one direction, whereas antiport rules move objects across a membrane in opposite directions.

From the seminal definition of Tissue P systems [15, 16], several research lines have been developed and other variants have arisen (see, for example, [2, 5, 7, 12, 13, 25]). One of the most interesting variants of Tissue P systems was presented in [21]. In that paper, the definition of Tissue P systems is combined with the one of P systems with active membranes, yielding *Tissue P systems with cell division*.

One of the main features of such Tissue P systems with cell division is related to their computational efficiency. In [21], a polynomial-time solution to the **NP**-complete problem SAT is shown. In this paper we go on with the research in this variant and present a linear-time solution to another well-known **NP**-complete problem: the 3-COL problem.

The paper is organized as follows: first we recall some preliminaries and the definition of Tissue P systems with cell division. Next, recognizer Tissue P systems are briefly described. A linear-time solution to the 3-COL problem is presented in the following section, with a short overview of the computation and the necessary resources. Finally, the main results, some conclusions and new open research lines are presented.

References

- [1] Alberts, B., Johnson, A., Lewis, J., Raff, M., Roberts, K. and Walter, P. *The Molecular Biology of the Cell*, Fourth Edition, Garland Publ. Inc., London (2002).
- [2] Alhazov, A., Freund, R. and Oswald, M. Tissue P Systems with Antiport Rules and Small Numbers of Symbols and Cells. In C. de Felice, A. Restivo (eds.). LNCS **3572**, (2005), 100–111.
- [3] Appel, K. and Haken, W. Every planar map is 4-colorable - 1: Discharging. *Illinois Journal of Mathematics* **21**, (1977), 429–490.
- [4] Appel, K. and Haken, W. Every planar map is 4-colorable - 2: Reducibility. *Illinois Journal of Mathematics* **21**, (1977), 491–567.
- [5] Bernardini, F. and Gheorghe, M. Cell Communication in Tissue P Systems and Cell Division in Population P Systems. *Soft Computing* **9**, 9, (2005), 640–649.
- [6] L. Cardelli. Brane Calculi. In V. Danos, V. Schachter (eds.). LNBI **3082**, (2005), 257–278.

²This way of communication for P systems was introduced in [19].

- [7] Freund, R., Păun, Gh. and Pérez-Jiménez, M.J. Tissue P Systems with channel states. *Theoretical Computer Science* **330**, (2005), 101–116.
- [8] Frisco, P. and Hoogeboom, H.J. Simulating counter automata by P systems with symport/antiport. In Gh. Păun, G. Rozenberg, A. Salomaa, C. Zandron, (eds.). LNCS **2597**, (2003), 288–301.
- [9] Garey, M.R. and Johnson, D.S. *Computers and Intractability A Guide to the Theory of NP-Completeness*. W.H. Freeman and Company, (1979).
- [10] Gutiérrez-Naranjo, M.A., Pérez-Jiménez, M.J., Romero-Campero, F.J. A linear solution for QSAT with Membrane Creation. In R. Freund, Gh. Păun, G. Rozenberg, A. Salomaa (eds.). LNCS **3850**, (2006), 241–252.
- [11] Ionescu, M., Păun, Gh. and Yokomori, T. Spiking neural P systems, submitted, (2005).
- [12] Krishna, S.N., Lakshmanan K. and Rama, R. Tissue P Systems with Contextual and Rewriting Rules. Gh. Păun, G. Rozenberg, A. Salomaa and C. Zandron (eds.). LNCS **2597**, (2003), 339–351.
- [13] Lakshmanan K. and Rama, R. On the Power of Tissue P Systems with Insertion and Deletion Rules. In A. Alhazov, C. Martín-Vide and Gh. Paun (eds.) *Preproceedings of the Workshop on Membrane Computing*, Tarragona, Report RGML 28/03, (2003), 304–318.
- [14] Luisi, P.L. The Chemical Implementation of Autopoiesis. In G.R. Fleishaker et al. (eds.) *Self-Production of Supramolecular Structures*, Kluwer, Dordrecht, (1994).
- [15] Martín Vide, C. Pazos, J. Păun, Gh. Rodríguez Patón, A. A New Class of Symbolic Abstract Neural Nets: Tissue P Systems. In O.H. Ibarra and L. Zhang (eds.). LNCS **2387**, (2002), 290–299.
- [16] Martín Vide, C. Pazos, J. Păun, Gh. and Rodríguez Patón, A. Tissue P systems. *Theoretical Computer Science*, **296**, (2003), 295–326.
- [17] Păun, Gh. Computing with membranes. *Journal of Computer and System Sciences*, **61**, 1, (2000), 108–143.
- [18] Păun, Gh. *Membrane Computing. An Introduction*. Springer-Verlag, Berlin, (2002).
- [19] Păun, A. Păun, Gh. The power of communication: P systems with symport/antiport. *New Generation Computing*, **20**, 3, (2002), 295–305.
- [20] Păun, Gh. and Pérez-Jiménez, M.J. Recent computing models inspired from biology: DNA and membrane computing. *Theoria*, **18**, 46, (2003), 72–84.

- [21] Păun, Gh. Pérez-Jiménez, M.J. and Riscos-Núñez, A. Tissue P System with cell division. In Gh. Păun, A. Riscos-Núñez, A. Romero-Jiménez, F. Sancho-Caparrini (eds.), *Second Brainstorming Week on Membrane Computing*, Sevilla, Report RGNC 01/2004, (2004), 380–386.
- [22] Pérez-Jiménez, M.J., Romero-Jiménez, A. and Sancho-Caparrini, F. *Teoría de la Complejidad en Modelos de Computación Celular con Membranas*. Editorial Kronos, Sevilla, (2002).
- [23] Pérez-Jiménez, M.J., Romero-Jiménez, A. and Sancho-Caparrini, F. The P versus NP problem through cellular computing with membranes. In N. Jonoska, Gh. Păun, Gr. Rozenberg (eds.). LNCS **2950**, (2004), 338–352.
- [24] Pérez-Jiménez, M.J. Romero-Jiménez, A. and Sancho-Caparrini, F. A polynomial complexity class in P systems using membrane division. In E. Csuhaj-Varjú, C. Kintala, D. Wotschke and Gy. Vaszyl (eds.), *Proceedings of the 5th Workshop on Descriptive Complexity of Formal Systems, DCFS 2003*, (2003), 284–294.
- [25] Prakash, V.J. On the Power of Tissue P Systems Working in the Maximal-One Mode. In A. Alhazov, C. Martín-Vide and Gh. Păun (eds.). *Preproceedings of the Workshop on Membrane Computing*, Tarragona, Report RGML 28/03, (2003), 356–364.
- [26] Stockmeyer, L.J. Planar 3-colorability is NP-complete. *SIGACT News* **5**, 3, (1973), 19–25.
- [27] Syropoulos, A. Mathematics of Multisets. In C.S. Calude, G. Păun, G. Rozenberg and A. Salomaa (eds.), LNCS **2235**, (2001), 347–358.
- [28] Zandron, C., Ferreti, C. and Mauri, G. Solving NP-Complete Problems Using P Systems with Active Membranes. In I. Antoniou, C.S. Calude and M.J. Dinneen (eds.). *Unconventional Models of Computation, UMC'2K*, Springer-Verlag, (2000), 289–301.
- [29] ISI web page <http://esi-topics.com/erf/october2003.html>
- [30] P systems web page <http://psystems.disco.unimib.it/>